

SAFETY DATA SHEET

Section 1. Product And Company Identification

Product Name: NX3 Nexus® Third Generation Dual Cure Base and Catalyst **Product Use:** Dental product: Permanent cement

Manufacturer: Kerr Corporation 1717 W. Collins Ave. Orange, CA 92867-5422 U.S.A.

Information Phone Number: 1-800-841-1428 (Customer Service)

Chemical Emergency Phone Number (Chemical Spills, Leaks, Fire, Exposure or Accident only): CHEMTREC 1-800-424-9300 (in the US) 1-703-527-3887 (Outside the US)

SDS Date of Preparation/Revision: April 15, 2019

Section 2. Hazards Identification

GHS Classification:

Eye Irritant Category 2A Skin Irritant Category 2 Skin Sensitizer Category 1

Label Elements:



Hazard Phrases:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary Phrases:

Avoid breathing dust.

Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves and eye protection.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Dispose of contents and container in accordance with local and national regulations.



Section 3. Composition/Information on Ingredients

The following ingredients are in the Base:

Component	CAS No.	Amount
Barium aluminoborosilicate glass	65997-17-3	30-60%
Ytterbium fluoride	13760-80-0	10-<30%
Ethoxylated bisphenol-A dimethacrylate	41637-38-1	<15%
Urethane dimethacrylate	72869-86-4	<10%
Triethylene glycol dimethacrylate	109-16-0	<10%
Hydroxyethylmethacrylate	868-77-9	<10%
Fumed silica	68909-20-6	<5%
Bisphenol-A diglycidyl methacrylate	1565-94-2	<5%
Ethyldimethylaminobenzoate	10287-53-3	<0.5%

The following ingredients are in the Catalyst:

Component	CAS No.	Amount	
Barium aluminoborosilicate glass	65997-17-3	30-60%	
Ytterbium fluoride	13760-80-0	10-<30%	
Triethylene glycol dimethacrylate	109-16-0	<10%	
Ethoxylated bisphenol-A dimethacrylate	41637-38-1	<10%	
Urethane dimethacrylate	72869-86-4	<10%	
Fumed silica	68909-20-6	<5%	
Bisphenol-A diglycidyl methacrylate	1565-94-2	<5%	
Hydroxyethylmethacrylate	868-77-9	<5%	
Peppermint oil	8006-90-4	<0.5%	

Section 4. First Aid Measures

Inhalation: Remove victim to fresh air. If breathing is difficult or irritation persists, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Flush skin thoroughly with water for several minutes. Get medical attention if irritation or rash occurs. Launder clothing before re-use.

Eye Contact: Immediately flush eyes with large quantities of water for several minutes, while holding the eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get medical attention if irritation persists.

Ingestion: Rinse mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if you feel unwell.

Most important symptoms and effects, acute and delayed: May cause moderate eye and skin irritation. May cause skin sensitization. Inhalation of dust from dried product or vapors may cause irritation of the mucous membranes and upper respiratory tract.

Indication of immediate medical attention and special treatment, if needed: Immediate medical attention is not required.



Section 5. Fire Fighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use any media appropriate for the surrounding fire. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: Combustion may produce carbon oxides, nitrogen oxides, phosphorus oxides, metal oxides, and halogenated compounds.

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored. Contain water used in firefighting from entering sewers or natural waterways.

Section 6: Accidental Release Measures

Personal precautions, Protective equipment, and Emergency procedures: Avoid contact with eyes, skin and clothing. Wear appropriate protective clothing and equipment. Avoid breathing dust from dried product or vapors.

Environmental Precautions: Avoid releases to the environment. Report spill as required by local and federal regulations.

Methods and Materials for Containment and Cleaning up: Collect material with an inert absorbent material and place in appropriate, labeled container for disposal.

Section 7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes, skin and clothing. Always wear impervious gloves, chemical safety goggles and protective clothing when handling this material. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke in the work area. Avoid breathing dust or vapors. Use with adequate ventilation. Remove and wash contaminated clothing before reuse. Empty containers retain product residues which can be hazardous. Follow all SDS precautions when handling empty containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, dry, well-ventilated area away from direct sunlight. Keep container tightly closed and sealed until ready to use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

Section 8. Exposure Controls / Personal Protection

Exposure Limits

Chemical	Exposure Limit
Barium aluminoborosilicate glass (as dust, general threshold limit value)	10 mg/m ³ TWA ACGIH TLV (total) 5 mg/m ³ TWA ACGIH TLV (inhalable fraction)
Ytterbium fluoride (as fluorides)	2.5 mg/m ³ TWA ACGIH TLV
Ethoxylated bisphenol-A dimethacrylate	None Established
Urethane dimethacrylate	None Established



NX3 Nexus® Third Generation Dual Cure Base and Catalyst 4/15/19

Triethylene glycol dimethacrylate	None Established
Hydroxyethylmethacrylate	None Established
Fumed silica (as amorphous silica)	10 mg/m ³ TWA ACGIH TLV (inhalable) 3 mg/m ³ TWA ACGIH TLV (respirable)
Bisphenol-A diglycidyl methacrylate	None Established
Ethyldimethylaminobenzoate	None Established
Peppermint oil	None Established

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

Respiratory Protection: In operations where exposure levels are exceeded, an approved dust/mist respirator or supplied air respirator should be used. Equipment selection depends on contaminant type and concentration. Select in accordance with applicable regulations and good industrial hygiene practice.

Hand protection: Impervious gloves are suggested to prevent skin contact. Contact your glove supplier for selection assistance.

Eye Protection: Chemical safety goggles are recommended if contact is possible.

Skin Protection: Wear protective clothing as needed to avoid skin contact and contamination of personal clothing.

Hygiene measures: Suitable eye and skin washing facilities should be available in the work area.

Section 9. Physical and Chemical Properties			
Appearance:	Colored paste of various colors	Odor:	Fruity ester-like odor
Odor Threshold:	Not available	pH:	Not available
Melting/Freezing	Not available	Boiling	Not available
Point:		Point/Range:	
Flash Point:	Not available	Evaporation	Not available
		Rate:	
Flammability: (Solid,	Not applicable	Flammability	LEL: Not applicable
Gas)		Limits:	UEL: Not applicable
Vapor Pressure:	Not available	Vapor	Not available
		Density:	
Relative Density:	2.0-2.5	Solubilities:	Insoluble in water
Partition Coefficient:	Not available	Autoignition	Not available
(N-Octanol/Water)		Temperature:	
Decomposition Temperature:	Not available	Viscosity:	Not available

Section 10. Stability and Reactivity

Reactivity: The product is not expected to be reactive.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: Heat can cause polymerization with rapid release of energy.



NX3 Nexus® Third Generation Dual Cure Base and Catalyst 4/15/19

Conditions to avoid: Keep away from flames, heat, and direct sunlight. **Incompatible Materials:** Oxidizing materials, reducing materials, amines, and peroxide. **Hazardous decomposition products:** Thermal decomposition will produce carbon oxides, nitrogen oxides, phosphorus oxides, metal oxides, and halogenated compounds.

Section 11. Toxicological Information

Potential Health Effects:

Inhalation: Inhalation of dust from dried product or vapors may cause nose, throat and upper respiratory tract.

Skin Contact: Direct contact may cause moderate skin irritation. May cause an allergic skin reaction. **Eye Contact:** Direct contact may cause moderate eye irritation.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. **Chronic Hazards:** None known.

Skin corrosion/irritation: This product is expected to cause skin irritation.

Eye damage/ irritation: This product is expected to cause eye irritation.

Skin Sensitization: Product is categorized in Grade I (weak sensitizer) in Kligman test.

Respiratory Sensitization: No data available. This product is not expected to cause respiratory sensitization.

Germ Cell Mutagenicity: This product is not expected to cause mutagenicity.

Carcinogen: None of the components are listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH, or OSHA.

Developmental / Reproductive Toxicity: This product is not classified as a reproductive hazard.

Specific Target Organ Toxicity (Single Exposure): No data available.

Specific Target Organ Toxicity (Repeated Exposure): No data available.

Aspiration Toxicity: Not an aspiration hazard.

Acute Toxicity Values:

Extruded Product ATE: >5000 mg/kg (oral), >5 mg/L (inhalation, as mist), >2000 mg/L (dermal) Barium aluminoborosilicate glass: Not toxic Ytterbium fluoride: Oral rat LD50: >2000 mg/kg Ethoxylated bisphenol-A dimethacrylate: Oral rat LD50: >2000 mg/kg, Skin rat LD50: >2000 mg/kg Urethane dimethacrylate: Oral rat LD50: >5000 mg/kg, Skin rat LD50: >2000 mg/kg Triethylene glycol dimethacrylate: Oral rat LD50: 8700 mg/kg Hydroxyethylmethacrylate Oral rat LD50: 5564 mg/kg, Skin rabbit LD50: >5000 mg/kg Fumed silica: Oral rat LD50: >5000 mg/kg, Inhalation rat LC0: >0.139 mg/L/4hr (no mortality), Skin rat LD50: >5000 mg/kg Bisphenol-A diglycidyl methacrylate: No toxicity data available Ethyldimethylaminobenzoate: Oral rat LD50: >2000 mg/kg, Skin rat LD50: >2000 mg/kg Peppermint oil: Oral rat LD50: 2650 mg/kg, Skin rabbit LD50: >5000 mg/kg



Section 12. Ecological Information

Toxicity:

Ytterbium fluoride: 48 hr EC50 Daphnia magna: >0.52 mg/L

Ethoxylated bisphenol-A dimethacrylate: 96hr LL50 Rainbow trout: >100 mg/L, 48hr EL50 Daphnia magna: 6 mg/L

Urethane dimethacrylate: 96hr LC50 Zebra fish: 10.1 mg/L, 48hr EC50 Daphnia magna: >1.2 mg/L, 72hr EC50 Desmodesmus subspicatus: >0.68 mg/L

Triethylene glycol dimethacrylate: 96hr LC50 Zebra fish: 16.4 mg/L, 21 day NOEC Daphnia magna: 32 mg/L

Hydroxyethylmethacrylate: 96hr LC50 Japanese Rice Fish: >100 mg/L, 48hr EC50 Daphnia magna: 380 mg/L, 21 day NOEC Daphnia magna: 24.1 mg/L

Ethyldimethylaminobenzoate: 96hr LC50 Rainbow trout: 1.9 mg/L, 48 hr EC50 Daphnia magna: 4.5 mg/L Peppermint oil: 96hr LC50 Fish: 3.40 mg/L (QSAR), 48hr EC50 Daphnia magna: 2.7 mg/L

This product is expected to be harmful to the aquatic environment. Releases to the environment should be avoided.

Persistence and degradability: Ethyldimethylaminobenzoate: Not readily biodegradable-40% in 28 days.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

Section 13. Disposal Considerations

Disposal: For unused product, dispose of in accordance with Federal and local regulations. **Container Disposal:** Dispose of empty container in accordance with Federal and local regulations.

Section 14. Transport Information

	UN Number	UN Proper Shipping Name	Hazard Class(s)	Packing Group	Environmental Hazards
US DOT	None	Not Regulated	None	None	None
EU	None	Not Regulated	None	None	None
ADR/RID					
IMDG	None	Not Regulated	None	None	None
IATA/ICAO	None	Not Regulated	None	None	None

Special Precautions for User: None identified

Transport in Bulk According to Annex II MARPOL 73/78 and the IBC Code: Not applicable – product is transported only in packaged form.

Section 15. Regulatory Information

U.S. Federal Regulations:



EPA SARA 311/312 Hazard Classification: Refer to Section 2 for OSHA Hazard Classification.

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

Protection Of Stratospheric Ozone: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: This product is not subject to CERCLA reporting requirements; however, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

International Inventories

US EPA TSCA Inventory: All of the components of this product are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory or exempt.

Canada CEPA: All of the components of this material are listed on the DSL or exempt.

Section 16. Other Information

Effective Date: April 15, 2019 Supersedes Date: May 15, 2015 Revision Summary: All Sections – New SDS format

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date of preparation, however, KERR Corporation makes no warranty with respect to the accuracy or suitability of the recommendations, and assumes no liability to any use thereof.